



[larger image](#)

### Type L6TF Teflon Immersion Heater

All GLO-QUARTZ® Teflon® immersion heaters consist of a heavy wall Teflon® tube extruded over a grounded stainless steel heating element. Shown below are some Standard heater configurations. Special Configurations are available. Maximum watt density 10 Watt/in<sup>2</sup>. Maximum operating temperature 90°C/195°F.

Results 1 - 8 of 8

1

<u>Item #</u>	<u>MAX. Immersion Length [A]</u>	<u>Heated Length [B]</u>	<u>KW</u>	<u>Ship Weight</u>	<u>Options</u>
<u>L6TF-2XX11-R12</u>	12"	11"	2	12	Longer "A" dimension Teflon Guard Available
<u>L6TF-3XX15-R18</u>	18"	15"	3	13	Longer "A" dimension Teflon Guard Available
<u>L6TF-4XX20-R18</u>	18"	20"	4	14	Longer "A" dimension Teflon Guard Available
<u>L6TF-5XX25-R18</u>	18"	25"	5	15	Longer "A" dimension Teflon Guard Available
<u>L6TF-6XX30-R18</u>	18"	30"	6	16	Longer "A" dimension Teflon Guard Available
<u>L6TF-7XX35-R18</u>	18"	35"	7	17	Longer "A" dimension Teflon Guard Available
<u>L6TF-8XX40-</u>	18"	40"	8	18	Longer "A" dimension

R18

L6TF-9XX45-  
R18

18"

45"

9

19

Teflon Guard  
Available

Longer "A"  
dimension  
Teflon Guard  
Available