



[larger image](#)

Process Heat Control TCD

GLO-QUARTZ® temperature control models TC1 and TCD are to be used with heaters equipped with an over-temperature sensor. Both models are combination controls. The functions of the various switches and pilot lights are outlined here.

Results 1 - 17 of 17

1

<u>Item #</u>	<u>Max Amps per Pole</u>	<u>208</u>	<u>220</u>	<u>240</u>	<u>440</u>	<u>480</u>
<u>TCD-230</u>	30	6.2 kW	6.6 kW	7.2 kW	N/A	N/A
<u>TCD-250</u>	50	10.4 kW	11 kW	12 kW	N/A	N/A
<u>TCD-270</u>	70	14.6 kW	15.4 kW	16.8 kW	N/A	N/A
<u>TCD-290</u>	90	18.7 kW	19.8 kW	21.6 kW	N/A	N/A
<u>TCD-2120</u>	120	24.9 kW	26.4 kW	28.8 kW	N/A	N/A
	N/A	N/A	N/A	N/A	N/A	N/A
<u>TCD-330</u>	30	10.4 kW	11.4 kW	12.4 kW	N/A	N/A
<u>TCD-350</u>	50	17.9 kW	19 kW	20.7 kW	N/A	N/A
<u>TCD-370</u>	70	25.3 kW	26.6 kW	28.9 kW	N/A	N/A
<u>TCD-390</u>	90	32.3 kW	34.2 kW	37.3 kW	N/A	N/A
<u>TCD-3120</u>	120	43.1 kW	45.6 kW	49.8 kW	N/A	N/A
	N/A	N/A	N/A	N/A	N/A	N/A
<u>TCD-3430</u>	30	N/A	N/A	N/A	22.8 kW	24.9 kW
<u>TCD-3450</u>	50	N/A	N/A	N/A	38 kW	41.5 kW
<u>TCD-3470</u>	70	N/A	N/A	N/A	53.2 kW	58.1 kW
<u>TCD-3490</u>	90	N/A	N/A	N/A	68.5 kW	74.7 kW
<u>TCD-34120</u>	120	N/A	N/A	N/A	91.3 kW	99.6 kW