

View Items

Check up to five results to perform an action.



[larger image](#)

Type L9 Bottom Heaters

Features:

- Heated section ("B" dimension) at tank bottom to allow natural heat convection.
- All wetted parts durably constructed of the same material for optimum corrosion resistance.
- Preset temperature sensor encased in a thermowell, standard on all models.
- 1" sludge legs standard, longer sludge legs available.
- Optional NEMA 4 or explosion resistant junction box available.
- Vertical riser ("A" dimension) 36" standard length, other lengths available.
- Straight-up vertical riser available as option.
- "A" Dimension is maximum immersion length.
- "B" Dimension is heated length. Solution should be kept 2" above the heated length at all times.

Results 1 - 22 of 22

1

<u>Item #</u>	<u>MAX. Immersion Length</u> [A]	<u>Heated Length</u> [B]	<u>Type</u>	<u>KW</u>	<u>Ship Weight</u>
L9**-9XX14	14"	36"	Standard Density	4.5	13
L9**-13XX20	20"	36"	Standard Density	6.75	17
L9**-18XX24	24"	36"	Standard Density	9	20
L9**-22XX30	30"	36"	Standard Density	11.25	24
L9**-27XX32	32"	36"	Standard Density	13.5	27
L9**-31.5XX36	36"	36"	Standard Density	15.75	30
L9**-36XX42	42"	36"	Standard Density	18	36

<u>L9**- 405XX47</u>	47"	48"	Standard Density	20.25	39
<u>L9**-45XX52</u>	52"	48"	Standard Density	22.5	45
<u>L9**-54XX57</u>	57"	48"	Standard Density	27	46
<u>L9**-63XX67</u>	67"	48"	Standard Density	31.5	52
<u>L9**-45XX14</u>	14"	36"	Low Density	4.5	13
<u>L9**- 675XX20</u>	20"	36"	Low Density	6.75	17
<u>L9**-9XX24</u>	24"	36"	Low Density	9	20
<u>L9**- 1125XX30</u>	30"	36"	Low Density	11.25	24
<u>L9**- 135XX32</u>	32"	36"	Low Density	13.5	27
<u>L9**- 1575XX36</u>	36"	36"	Low Density	15.75	30
<u>L9**-18XX42</u>	42"	36"	Low Density	18	36
<u>L9**- 2025XX47</u>	47"	48"	Low Density	20.25	39
<u>L9**- 225XX52</u>	52"	48"	Low Density	22.5	45
<u>L9**-27XX57</u>	57"	48"	Low Density	27	46
<u>L9**- 315XX67</u>	67"	48"	Low Density	31.5	52