



[larger image](#)

Over-the-Side Type W Heaters

Features:

- Lightest per KW of any heater on the market
- Lowest watt density rating to reduce build-up and prolong heater life.
- Electropolish available to reduce corrosion.
- Preset over-temperature sensor standard.
- Moisture resistant junction box fully welded
- Permanently mounted tag allowing easy identification.
- Most sizes IN STOCK available for immediate delivery.
- Sheath materials available: SA=304 Stainless Steel, SB=316 Stainless Steel, N-Incoloy®, T-Titanium.

Results 1 - 22 of 22

1

<u>Item #</u>	<u>MAX. Immersion Length</u> [A]	<u>Heated Length</u> [B]	<u>Type</u>	<u>KW</u>	<u>Ship Weight</u>
<u>W**-1XX18</u>	18"	10"	Standard Density	1	2
<u>W**-15XX22</u>	22"	14"	Standard Density	1.5	2.5
<u>W**-2XX28</u>	28"	20"	Standard Density	2	3
<u>W**-25XX30</u>	30"	22"	Standard Density	2.5	3.5
<u>W**-3XX34</u>	34"	26"	Standard Density	3	4
<u>W**-35XX40</u>	40"	30"	Standard Density	3.5	4.5
<u>W**-4XX45</u>	45"	35"	Standard Density	4	5
<u>W**-45XX50</u>	50"	40"	Standard Density	4.5	5.5
<u>W**-5XX55</u>	55"	45"	Standard Density	5	6

<u>W**-6XX65</u>	65"	55"	Standard Density	6	6.5
<u>W**-7XX70</u>	70"	60"	Standard Density	7	7
<u>W**-5XX18</u>	18"	10"	Low Density	.5	2
<u>W**-75XX22</u>	22"	14"	Low Density	.75	2.5
<u>W**-1XX28</u>	28"	20"	Low Density	1	3
<u>W**- 125XX30</u>	30"	22"	Low Density	1.25	3.5
<u>W**-15XX34</u>	34"	26"	Low Density	1.5	4
<u>W**- 175XX40</u>	40"	30"	Low Density	1.75	4.5
<u>W**-2XX45</u>	45"	35"	Low Density	2	5
<u>W**- 225XX50</u>	50"	40"	Low Density	2.25	5.5
<u>W**-25XX55</u>	55"	45"	Low Density	2.5	6
<u>W**-3XX65</u>	65"	55"	Low Density	3	6.5
<u>W**-35XX70</u>	70"	60"	Low Density	3.5	7