

Type W3 Over the Side Heaters

Features:



[larger image](#)

- Lightest per KW of any heater on the market
- Lowest watt density rating to reduce build-up and prolong heater life.
- Electropolish available to reduce corrosion.
- Preset over-temperature sensor standard.
- Moisture resistant junction box fully welded
- Permanently mounted tag allowing easy identification.
- Most sizes IN STOCK available for immediate delivery.
- Sheath materials available: SA=304 Stainless Steel, SB=316 Stainless Steel, N-Incoloy®, T-Titanium.

Results 1 - 22 of 22

1

<u>Item #</u>	<u>MAX. Immersion Length</u> <u>[A]</u>	<u>Heated Length</u> <u>[B]</u>	<u>Type</u>	<u>KW</u>	<u>Ship Weight</u>
<u>W3**-3XX18</u>	18"	10"	Standard Density	1.5	4
<u>W3**-45XX22</u>	22"	14"	Standard Density	2.25	6
<u>W3**-6XX28</u>	28"	20"	Standard Density	3	7
<u>W3**-75XX30</u>	30"	22"	Standard Density	3.75	9
<u>W3**-9XX34</u>	34"	26"	Standard Density	4.5	10
<u>W3**-105XX40</u>	40"	30"	Standard Density	5.25	12
<u>W3**-12XX45</u>	45"	35"	Standard Density	6	13
<u>W3**-135XX50</u>	50"	40"	Standard Density	6.75	15
<u>W3**-15XX55</u>	55"	45"	Standard Density	7.5	16

<u>W3**- 18XX65</u>	65"	55"	Standard Density	9	18
<u>W3**- 21XX70</u>	70"	60"	Standard Density	10.5	19
<u>W3**- 15XX18</u>	18"	10"	Low Density	1.5	4
<u>W3**- 225XX22</u>	22"	14"	Low Density	2.25	6
<u>W3**-3XX28</u>	28"	20"	Low Density	3	7
<u>W3**- 375XX30</u>	30"	22"	Low Density	3.75	9
<u>W3**- 45XX34</u>	34"	26"	Low Density	4.5	10
<u>W3**- 525XX40</u>	40"	30"	Low Density	5.25	12
<u>W3**-6XX45</u>	45"	35"	Low Density	6	13
<u>W3**- 675XX50</u>	50"	40"	Low Density	6.75	15
<u>W3**- 75XX55</u>	55"	45"	Low Density	7.5	16
<u>W3**-9XX65</u>	65"	55"	Low Density	9	18
<u>W3**- 105XX70</u>	70"	60"	Low Density	10.5	19