



Type W6 Over the Side Heaters

Features:

- Lightest per KW of any heater on the market
- Lowest watt density rating to reduce build-up and prolong heater life.
- Electropolish available to reduce corrosion.
- Preset over-temperature sensor standard.
- Moisture resistant junction box fully welded
- Permanently mounted tag allowing easy identification.
- Most sizes IN STOCK available for immediate delivery.
- Sheath materials available: SA=304 Stainless Steel, SB=316 Stainless Steel, N-Incoloy®, T-Titanium.

[larger image](#)

Results 1 - 22 of 22

1

<u>Item #</u>	<u>MAX. Immersion Length</u> <u>[A]</u>	<u>Heated Length</u> <u>[B]</u>	<u>Type</u>	<u>KW</u>	<u>Ship Weight</u>
<u>W6**-6XX18</u>	18"	10"	Standard Density	3	5
<u>W6**-9XX22</u>	22"	14"	Standard Density	4.5	7
<u>W6**-12XX28</u>	28"	20"	Standard Density	6	8
<u>W6**-15XX30</u>	30"	22"	Standard Density	7.5	11
<u>W6**-18XX34</u>	34"	26"	Standard Density	9	14
<u>W6**-21XX40</u>	40"	30"	Standard Density	10.5	17
<u>W6**-24XX45</u>	45"	35"	Standard Density	12	20
<u>W6**-27XX50</u>	50"	40"	Standard Density	13.5	23
<u>W6**-30XX55</u>	55"	45"	Standard Density	15	26

<u>W6**-36XX65</u>	65"	55"	Standard Density	18	29
<u>W6**-42XX70</u>	70"	65"	Standard Density	21	32
<u>W6**-3XX18</u>	18"	10"	Low Density	3	5
<u>W6**-45XX22</u>	22"	14"	Low Density	4.5	7
<u>W6**-6XX28</u>	28"	20"	Low Density	6	8
<u>W6**-75XX30</u>	30"	22"	Low Density	7.5	11
<u>W6**-9XX34</u>	34"	26"	Low Density	9	14
<u>W6**105XX40</u>	40"	30"	Low Density	10.5	17
<u>W6**-12XX45</u>	45"	35"	Low Density	12	20
<u>W6**- 135XX50</u>	50"	40"	Low Density	13.5	23
<u>W6**-15XX55</u>	55"	45"	Low Density	15	26
<u>W6**-18XX65</u>	65"	55"	Low Density	18	29
<u>W6**-21XX70</u>	70"	65"	Low Density	21	32