



## Type W9 Over the Side Heaters

Features:

- Lightest per KW of any heater on the market
- Lowest watt density rating to reduce build-up and prolong heater life.
- Electropolish available to reduce corrosion.
- Preset over-temperature sensor standard.
- Moisture resistant junction box fully welded
- Permanently mounted tag allowing easy identification.
- Most sizes IN STOCK available for immediate delivery.
- Sheath materials available: SA=304 Stainless Steel, SB=316 Stainless Steel, N-Incoloy®, T-Titanium.

[larger image](#)

Results 1 - 22 of 22

1

<u>Item #</u>	<u>MAX. Immersion Length [A]</u>	<u>Heated Length [B]</u>	<u>Type</u>	<u>KW</u>	<u>Ship Weight</u>
<u>W9**-9XX18</u>	18"	10"	Standard Density	4.5	10
<u>W9**-135XX22</u>	22"	14"	Standard Density	6.75	11
<u>W9**-18XX28</u>	28"	20"	Standard Density	9	12
<u>W9**-225XX30</u>	30"	22"	Standard Density	11.25	17
<u>W9**-27XX34</u>	34"	26"	Standard Density	13.5	21
<u>W9**-315XX40</u>	40"	30"	Standard Density	15.75	24
<u>W9**36XX45</u>	45"	35"	Standard Density	18	28
<u>W9**-405XX50</u>	50"	40"	Standard Density	20.25	23
<u>W9**-45XX55</u>	55"	45"	Standard Density	22.5	36

<u>W9**-54XX65</u>	65"	55"	Standard Density	27	40
<u>W9**-63XX70</u>	70"	60"	Standard Density	31.5	44
<u>W9**-45XX18</u>	18"	10"	Low Density	4.5	10
<u>W9**-675XX22</u>	22"	14"	Low Density	6.75	11
<u>W9**-9XX28</u>	28"	20"	Low Density	9	12
<u>W9**- 1125XX30</u>	30"	22"	Low Density	11.25	17
<u>W9**-135XX34</u>	34"	26"	Low Density	13.5	21
<u>W9**- 1575XX40</u>	40"	30"	Low Density	15.75	24
<u>W9**-18XX45</u>	45"	35"	Low Density	18	28
<u>W9**- 2025XX50</u>	50"	40"	Low Density	20.25	23
<u>W9**-225XX55</u>	55"	45"	Low Density	22.5	36
<u>W9**-27XX65</u>	65"	55"	Low Density	27	40
<u>W9**-315XX70</u>	70"	60"	Low Density	31.5	44