

Type L Bottom Heaters

Features:

- Heated section ("B" dimension) at tank bottom to allow natural heat convection.
- All wetted parts durably constructed of the same material for optimum corrosion resistance.
- Preset temperature sensor encased in a thermowell, standard on all models.
- 1" sludge legs standard, longer sludge legs available.
- Optional NEMA 4 or explosion resistant junction box available.
- Vertical riser ("A" dimension) 36" standard length, other lengths available.
- Straight-up vertical riser available as option.
- "A" Dimension is maximum immersion length.
- "B" Dimension is heated length. Solution should be kept 2" above the heated length at all times.



[larger image](#)

Results 1 - 22 of 22

1

| <u>Item #</u> | <u>MAX. Immersion Length</u> <u>[A]</u> | <u>Heated Length</u> <u>[B]</u> | <u>Type</u> | <u>KW</u> | <u>Ship Weight</u> |
|-------------------|--|------------------------------------|------------------|-----------|--------------------|
| <u>L**-1XX14</u> | 14" | 36" | Standard Density | .5 | 5 |
| <u>L**-15XX20</u> | 20" | 36" | Standard Density | .75 | 6 |
| <u>L**-2XX24</u> | 24" | 36" | Standard Density | 1 | 7 |
| <u>L**-25XX30</u> | 30" | 36" | Standard Density | 1.25 | 8 |
| <u>L**-3XX32</u> | 32" | 36" | Standard Density | 1.5 | 9 |
| <u>L**-35XX36</u> | 36" | 36" | Standard Density | 1.75 | 10 |
| <u>L**-4XX42</u> | 42" | 36" | Standard Density | 2 | 11 |

| | | | | | |
|-------------------------|-----|-----|------------------|------|----|
| <u>L**-45XX47</u> | 47" | 48" | Standard Density | 2.25 | 13 |
| <u>L**-5XX52</u> | 52" | 48" | Standard Density | 2.5 | 14 |
| <u>L**-6XX57</u> | 57" | 48" | Standard Density | 3 | 15 |
| <u>L**-7XX67</u> | 67" | 48" | Standard Density | 3.5 | 16 |
| <u>L**-5XX14</u> | 14" | 36" | Low Density | .5 | 5 |
| <u>L**-75XX20</u> | 20" | 36" | Low Density | .75 | 6 |
| <u>L**-1XX24</u> | 24" | 36" | Low Density | 1 | 7 |
| <u>L**- 125XX30</u> | 30" | 36" | Low Density | 1.25 | 8 |
| <u>L**-15XX32</u> | 32" | 36" | Low Density | 1.5 | 9 |
| <u>L**- 175XX36</u> | 36" | 36" | Low Density | 1.75 | 10 |
| <u>L**-2XX42</u> | 42" | 36" | Low Density | 2 | 11 |
| <u>L**- 225XX47</u> | 47" | 48" | Low Density | 2.25 | 13 |
| <u>L**-25XX52</u> | 52" | 48" | Low Density | 2.5 | 14 |
| <u>L**-3XX57</u> | 57" | 48" | Low Density | 3 | 15 |
| <u>L**-35XX67</u> | 67" | 48" | Low Density | 3.5 | 16 |