

Type L3 Bottom Heaters

Features:

- Heated section ("B" dimension) at tank bottom to allow natural heat convection.
- All wetted parts durably constructed of the same material for optimum corrosion resistance.
- Preset temperature sensor encased in a thermowell, standard on all models.
- 1" sludge legs standard, longer sludge legs available.
- Optional NEMA 4 or explosion resistant junction box available.
- Vertical riser ("A" dimension) 36" standard length, other lengths available.
- Straight-up vertical riser available as option.
- "A" Dimension is maximum immersion length.
- "B" Dimension is heated length. Solution should be kept 2" above the heated length at all times.



[larger image](#)

Results 1 - 22 of 22

1

<u>Item #</u>	<u>MAX. Immersion Length</u> <u>[A]</u>	<u>Heated Length</u> <u>[B]</u>	<u>Type</u>	<u>KW</u>	<u>Ship Weight</u>
L3**-3XX14	14"	36"	Standard Density	1.5	7
L3**-45XX20	20"	36"	Standard Density	2.25	8
L3**-6XX24	24"	36"	Standard Density	3	9
L3**-75XX30	30"	36"	Standard Density	3.75	11
L3**-9XX32	32"	36"	Standard Density	4.5	12
L3**-105XX36	36"	36"	Standard Density	5.25	13
L3**-12XX42	42"	36"	Standard Density	6	15

<u>L3**- 135XX47</u>	47"	48"	Standard Density	6.75	17
<u>L3**-15XX52</u>	52"	48"	Standard Density	7.5	19
<u>L3**-18XX57</u>	57"	48"	Standard Density	9	20
<u>L3**-21XX67</u>	67"	48"	Standard Density	10.5	21
<u>L3**-15XX14</u>	14"	36"	Low Density	1.5	7
<u>L3**- 225XX20</u>	20"	36"	Low Density	2.25	8
<u>L3**-3XX24</u>	24"	36"	Low Density	3	9
<u>L3**- 375XX30</u>	30"	36"	Low Density	3.75	11
<u>L3**-45XX32</u>	32"	36"	Low Density	4.5	12
<u>L3**- 525XX36</u>	36"	36"	Low Density	5.25	13
<u>L3**-6XX42</u>	42"	36"	Low Density	6	15
<u>L3**- 675XX47</u>	47"	48"	Low Density	6.75	17
<u>L3**-75XX52</u>	52"	48"	Low Density	7.5	19
<u>L3**-9XX57</u>	57"	48"	Low Density	9	20
<u>L3**- 105XX67</u>	67"	48"	Low Density	10.5	21